## **Specifications**

Model		WK-7500	CTK-7000
Keyboard		76 piano-style keys	61 piano-style keys
	Touch Response	2 sensitivity	
Sound Source		AHL (Tri-element)	
Polyphony (Maximum) Built-in Tones		64	
Built-in Tones	Stereo Sampled Piano Tones	800 (including 50 Drawbar Organ tones)	
User Tones		100 (Tone Editor) + 50 (Drawbar Organ)	
Drawbar Organ Function		9 drawbars (16', 5 1/3', 8', 4', 2 2/3', 2', 1 3/5', 1 1/3', 1')	
Built-in Drawbar Orga		50 (included in 800 built-in tones)	
	User Drawbar Organ Tones	50	
	Percussion	Second	
	Click Betany Effect	On /	
Digital Effects	Rotary Effect Reverb	Fast / Slow (Uses DSP.) 10 types	
	Chorus	5 types (simultaneous use with DSP not supported)	
	DSP	100 built-in, 100 user (simultaneous use with Chorus not supported)	
Built-in Rhythms	•	250	
•	Ethnic Rhythms (Latin / Other)	106 (39 / 67)	
	For Piano Play	20 400 (D. III.	
User Rhythms		100 (Pattern Sequencer) CASIO chord, Fingered 1, Fingered 2 (6th off), Fingered 3 (on bass),	
Auto Accompaniment		Full Range Chord	(otn oπ), Fingered 3 (on bass),
•	0	Start/Stop, Intro, Normal/Fill-in, Variation/Fill-in,	
	Controllers	Synchro/Ending (accompaniment volume adjustable)	
Pattern Sequencer		Real-time recording, step recording, quantize, Easy Edit,	
Pattern Sequencer		Event Editor, part parameters (100 user rhythms)	
Song Sequencer		Real-time recording (Easy Rec, Multi-track Rec), step recording, song edit,	
3 1	Llear Song	track edit, event edit (deléte, copy, insert, quantize), punch-in/out 5 songs, 17 tracks per song (1 system track + 16 multi tracks)	
	User Song Approximate Capacity	30,000 notes (	5 songs total)
Demonstration Songs	Approximate Capacity	50,000 Hotes (	o songs total)
<u> </u>		Play/Stop, Fast Forward, F	Fast Backward, Pause,
Song Controller		Repeat (song volume adjustable)	
Metronome		0, 2, 3, 4,	
	Tempo Range	30 to 255 per minute (tempo adjustable by tapping beat)	
Audio Recording / Playback	Recording Source	Keyboard play, keyboard play with Auto Accompaniment and with Music Preset, Song Sequencer playback, sound input from EXT IN (INST IN, MIC IN)	
		Up to 5 audio files	
	Recording Capacity	(maximum recording time: approximate	elv 13 minutes for a single audio file)
	Requirement	SD or SDHC memory card, 2GB to 32GB	
Mixer		32 channels + EXT IN (INST IN, MIC IN), 9-slider operation	
Registration		6 sets × 16 banks (96 setups) 305 presets with chord progression, chord edit	
Music Presets	Lloor Droceto		
One Touch Presets	User Presets	10 25	
Auto Harmonizing		12 types	
Arpeggiator		150 types	
Scale Tuning		Equal temperament + 16 preset scales, Scale Fine Tune	
Octave Shift		±2 octaves	
Layer		() (anish la anlit naist)	
Split Vov. Transpage		(variable split point)	
Key Transpose Tuning Control		±1 octave (-12 to +12 semitones) A4 = 415.5 - 440.0 - 456.9Hz	
Pitch Bend Wheel		Ditable hand non-new O.t. 40 annits and	
Modulation Button		Pitch bend range: 0 to 12 semitones	
Sliders		9	<u> </u>
Dial			
Display		LCD with backlight  16 channel multi-timbre received, GM Level 1 standard 1	
MIDI <sup>T</sup>	Cupported Memor: Card		
SD Memory Card Slot	Supported Memory Card	SD or SDHC memory SMF playback (up to 320k	/ Valu, 200 10 3200 (Rings file) file storage
	Functions	file recall, file delete, card f	format
	Seve / Lead	Registration setups, user rhythms, us	er tones, user drawbar organ tones.
	Save / Load	user DSPs, user music presets, song	
Terminals	USB <sup>2</sup>	● <sup>2</sup>	
	PHONES	(Stereo standard jack)	
	LINE OUT	(L/MONO, R for each; Standard jack) ♠ (Mono standard jack)	
	INST IN MIC IN	(Mono standard jack)     (Mono standard jack)	
	AUDIO IN	● (Mono standard jack) ● (Stereo mini jack)	
	SUSTAIN/ASSIGNABLE	(Stereo mini jack)  (Standard jack)	
	DC IN	● (Standard Jack)  • (12V)	
Speakers	Size	12cm × 2 + 3cm × 2	
	Bass-reflex System	•	
Speaker ON / OFF		•	
Amplifier Power		7W + 7W	
Power Size (M v D v H)		Batteries: D size x 6 / AC Adaptor: AD-A12150LW 1,187 x 399 x 149mm 945 x 378 x 132mm	
Size (W x D x H) Weight		,	
Accessories		8.9kg 6.8kg AC adaptor (AD-A12150LW), music stand	
ACCESSUITES		AO adapidi (AD-A12	100=11/, ITIUOIO SIGITU

 <sup>\*1</sup> These products are not equipped with MIDI terminals. MIDI communication between the product and a computer is performed using the USB port.
 \*2 Supported operating systems: Windows® XP Home Edition (SP2 or later), Windows® XP Professional (SP2 or later, 32-bit), Windows Vista® (32-bit), Windows® 7 (32-bit, 64-bit), Mac OS® X (10.3.9, 10.4.11 or later, 10.5.8 or later, 10.6.3 or later)
 A USB cable is not included with this product. To connect this product to a computer, use a commercially available A-B type USB cable.